

**FAG****618/1500-MA**

Deep groove ball bearing

Deep groove ball bearing 618..-MA, single row, solid brass cage

Technical information



Your current product variant

Sealing	Without	Not sealed
Cage	MA	Solid brass cage, outer ring guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	1.500 mm	Bore diameter
D	1.820 mm	Outside diameter
B	140 mm	Width
C _r	1.170.000 N	Basic dynamic load rating, radial
C _{0r}	3.750.000 N	Basic static load rating, radial
C _{ur}	57.000 N	Fatigue load limit, radial
n _G	530 1/min	Limiting speed
n _{gr}	315 1/min	Reference speed
m	756 kg	Weight



Mounting dimensions

$d_{a \min}$	1.528 mm	Minimum diameter shaft shoulder
$D_{a \max}$	1.792 mm	Maximum diameter of housing shoulder
$r_{a \max}$	6 mm	Maximum fillet radius

Dimensions

r_{\min}	7,5 mm	Minimum chamfer dimension
D_1	1.718,7 mm	Shoulder diameter outer ring
d_1	1.604,9 mm	Shoulder diameter inner ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Calculation factors

f_0	15,8	Calculation factor
-------	------	--------------------

Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed



Large bearing