

**FAG****61909**

Deep groove ball bearing

Deep groove ball bearing 619, single row,
steel sheet metal cage

Technical information



Your current product variant

| | | |
|----------------------------------|--------------|---|
| Type of Seal | Without | Not sealed |
| Cage | JN | Steel sheet metal |
| Tolerance class | PN | Normal (ISO 492:2023) |
| Dimensional / heat stabilization | SN | Rings dimensional stabilized up to 120° |
| Lubricant | Without | Bearing not greased |
| Radial internal clearance | CN (Group N) | Normal internal clearance |
| Bore type | Z | Cylindrical |

Main Dimensions & Performance Data

| | | |
|----------|--------------|-----------------------------------|
| d | 45 mm | Bore diameter |
| D | 68 mm | Outside diameter |
| B | 12 mm | Width |
| C_r | 15.000 N | Basic dynamic load rating, radial |
| C_{0r} | 10.900 N | Basic static load rating, radial |
| C_{ur} | 650 N | Fatigue load limit, radial |
| n_G | 14.400 1/min | Limiting speed |
| n_{gr} | 8.800 1/min | Reference speed |
| m | 0,136 kg | Weight |



Mounting dimensions

| | | |
|--------------|---------|--------------------------------------|
| $d_{a \min}$ | 48,2 mm | Minimum diameter shaft shoulder |
| $D_{a \max}$ | 64,8 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 0,6 mm | Maximum fillet radius |

Dimensions

| | | |
|------------|----------|------------------------------|
| r_{\min} | 0,6 mm | Minimum chamfer dimension |
| D_1 | 60,74 mm | Shoulder diameter outer ring |
| d_1 | 52,4 mm | Shoulder diameter inner ring |


Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 120 °C | Operating temperature max. |

Calculation factors

| | | |
|-------|----|--------------------|
| f_0 | 16 | Calculation factor |
|-------|----|--------------------|

Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed