

**FAG****61960-M**

Deep groove ball bearing

Deep groove ball bearing 619..-M, single row, solid brass cage

Technical information



Your current product variant

Type of Sealing	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	300 mm	Bore diameter
D	420 mm	Outside diameter
B	56 mm	Width
C _r	290.000 N	Basic dynamic load rating, radial
C _{0r}	400.000 N	Basic static load rating, radial
C _{ur}	12.800 N	Fatigue load limit, radial
n _G	2.600 1/min	Limiting speed
n _{gr}	1.890 1/min	Reference speed
m	23,8 kg	Weight



Mounting dimensions

$d_{a \min}$	312,4 mm	Minimum diameter shaft shoulder
$D_{a \max}$	407,6 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum fillet radius

Dimensions

r_{\min}	3 mm	Minimum chamfer dimension
D_1	384,15 mm	Shoulder diameter outer ring
d_1	337,1 mm	Shoulder diameter inner ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Calculation factors

f_0	16,2	Calculation factor
-------	------	--------------------

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing