

**FAG****61960-MA-C3**

Deep groove ball bearing

Deep groove ball bearing 619..-MA, single row, solid brass cage

## Technical information



## Your current product variant

Sealing	Without	Not sealed
Cage	MA	Solid brass cage, outer ring guided
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	300 mm	Bore diameter
D	420 mm	Outside diameter
B	56 mm	Width
$C_r$	290.000 N	Basic dynamic load rating, radial
$C_{0r}$	400.000 N	Basic static load rating, radial
$C_{ur}$	12.800 N	Fatigue load limit, radial
$n_G$	2.600 1/min	Limiting speed
$n_{gr}$	1.890 1/min	Reference speed
$m$	24,8 kg	Weight



### Mounting dimensions

$d_{a \min}$	312,4 mm	Minimum diameter shaft shoulder
$D_{a \max}$	407,6 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
$D_1$	385,1 mm	Shoulder diameter outer ring
$d_1$	337,1 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Calculation factors

$f_0$	16,2	Calculation factor
-------	------	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing