

**FAG****6220-2RSR-J20AA-C3**

Deep groove ball bearing

Deep groove ball bearing 62...-2RSR-J20AA, single row, seals, steel sheet metal cage, ceramic coated

## Technical information



## Your current product variant

Type of Seal	2RSR	Contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	GA13	Ball bearing and insert bearing grease
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical
Coating	J20AA	Current insulation, outer ring ceramic coated

## Main Dimensions &amp; Performance Data

d	100 mm	Bore diameter
D	180 mm	Outside diameter
B	34 mm	Width
C <sub>r</sub>	130.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	93.000 N	Basic static load rating, radial
C <sub>ur</sub>	5.500 N	Fatigue load limit, radial
n <sub>G</sub>	2.140 1/min	Limiting speed
≈m	3,14 kg	Weight



### Mounting dimensions

$d_{a \min}$	112 mm	Minimum diameter shaft shoulder
$D_{a \max}$	168 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	2,1 mm	Minimum chamfer dimension
$D_1$	155,45 mm	Shoulder diameter outer ring
$D_2$	158,9 mm	Caliber diameter outer ring
$d_1$	124,7 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

### Calculation factors

$f_0$	14,4	Calculation factor
-------	------	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides
	Current insulated