

**FAG****6224-2RSR-C3**

Deep groove ball bearing

Deep groove ball bearing 62...-2RSR, single row, seals, steel sheet metal cage

Technical information

**Your current product variant**

| | | |
|----------------------------------|--------------|---|
| Type of Seal | 2RSR | Contact seal on both sides |
| Cage | JN | Steel sheet metal |
| Tolerance class | PN | Normal (PN) |
| Dimensional / heat stabilization | S0 | Rings dimensional stabilized up to 150° |
| Lubricant | GA13 | Ball bearing and insert bearing grease |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Bore type | Z | Cylindrical |

Main Dimensions & Performance Data

| | | |
|-----------------|-------------|-----------------------------------|
| d | 120 mm | Bore diameter |
| D | 215 mm | Outside diameter |
| B | 40 mm | Width |
| C _r | 154.000 N | Basic dynamic load rating, radial |
| C _{0r} | 123.000 N | Basic static load rating, radial |
| C _{ur} | 6.400 N | Fatigue load limit, radial |
| n _G | 1.770 1/min | Limiting speed |
| m | 5,72 kg | Weight |

Mounting dimensions

| | | |
|--------------------|--------|--------------------------------------|
| d _{a min} | 132 mm | Minimum diameter shaft shoulder |
| D _{a max} | 203 mm | Maximum diameter of housing shoulder |
| r _{a max} | 2,1 mm | Maximum fillet radius |



Dimensions

| | | |
|------------|-----------|------------------------------|
| r_{\min} | 2,1 mm | Minimum chamfer dimension |
| D_1 | 185,04 mm | Shoulder diameter outer ring |
| D_2 | 190,5 mm | Caliber diameter outer ring |
| d_1 | 151,05 mm | Shoulder diameter inner ring |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -20 °C | Operating temperature min. |
| T_{\max} | 100 °C | Operating temperature max. |

Calculation factors

| | | |
|-------|------|--------------------|
| f_0 | 14,8 | Calculation factor |
|-------|------|--------------------|

Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides