

**FAG****6321-M-J20GA-C3**

Deep groove ball bearing

Deep groove ball bearing 63...-M-J20GA,  
single row, solid brass cage, ceramic coated

## Technical information



## Your current product variant

Sealing	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical
Coating	J20GA	Current insulation, outer ring ceramic coated

## Main Dimensions &amp; Performance Data

d	105 mm	Bore diameter
D	225 mm	Outside diameter
B	49 mm	Width
C <sub>r</sub>	188.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	150.000 N	Basic static load rating, radial
C <sub>ur</sub>	8.100 N	Fatigue load limit, radial
n <sub>G</sub>	5.300 1/min	Limiting speed
n <sub>gr</sub>	4.450 1/min	Reference speed
≈m	9,63 kg	Weight



### Mounting dimensions

$d_{a \min}$	119 mm	Minimum diameter shaft shoulder
$D_{a \max}$	211 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
$D_1$	188,5 mm	Shoulder diameter outer ring
$d_1$	144,3 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Calculation factors

$f_0$	13,7	Calculation factor
-------	------	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Current insulated