

**FAG****6248-M-C4**

Deep groove ball bearing

Deep groove ball bearing 62...-M, single row,  
solid brass cage

## Technical information



## Your current product variant

Type of Seal	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	240 mm	Bore diameter
D	440 mm	Outside diameter
B	72 mm	Width
$C_r$	360.000 N	Basic dynamic load rating, radial
$C_{0r}$	470.000 N	Basic static load rating, radial
$C_{ur}$	17.200 N	Fatigue load limit, radial
$n_G$	2.600 1/min	Limiting speed
$n_{gr}$	1.980 1/min	Reference speed
$m$	51,3 kg	Weight



### Mounting dimensions

$d_{a \min}$	257 mm	Minimum diameter shaft shoulder
$D_{a \max}$	423 mm	Maximum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
$D_1$	369,65 mm	Shoulder diameter outer ring
$d_1$	309,8 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Calculation factors

$f_0$	15,2	Calculation factor
-------	------	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing