

**FAG****6214-RSR-C3**

Deep groove ball bearing

Deep groove ball bearing 62...-RSR, single row, seal, steel sheet metal cage

## Technical information

**Your current product variant**

Sealing	RSR	Contact seal on one side
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

**Main Dimensions & Performance Data**

d	70 mm	Bore diameter
D	125 mm	Outside diameter
B	24 mm	Width
C <sub>r</sub>	66.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	44.000 N	Basic static load rating, radial
C <sub>ur</sub>	3.000 N	Fatigue load limit, radial
n <sub>G</sub>	3.100 1/min	Limiting speed
m	1,076 kg	Weight

**Mounting dimensions**

d <sub>a min</sub>	79 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	116 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	1,5 mm	Maximum fillet radius



### Dimensions

$r_{\min}$	1,5 mm	Minimum chamfer dimension
$D_1$	108,21 mm	Shoulder diameter outer ring
$D_2$	110,72 mm	Caliber diameter outer ring
$d_1$	86,75 mm	Shoulder diameter inner ring







### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

### Calculation factors

$f_0$	14,4	Calculation factor
-------	------	--------------------

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Sealed on one side