

**FAG****6317-2RSR-C3**

Deep groove ball bearing

Deep groove ball bearing 63...2RSR, single row, seals, steel sheet metal cage

## Technical information



## Your current product variant

Sealing	2RSR	Contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	GA13	Ball bearing and insert bearing grease
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	85 mm	Bore diameter
D	180 mm	Outside diameter
B	41 mm	Width
C <sub>r</sub>	141.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	97.000 N	Basic static load rating, radial
C <sub>ur</sub>	6.000 N	Fatigue load limit, radial
n <sub>G</sub>	2.350 1/min	Limiting speed
m	4,38 kg	Weight

## Mounting dimensions

d <sub>a min</sub>	99 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	166 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	2,5 mm	Maximum fillet radius



### Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
$D_1$	151,58 mm	Shoulder diameter outer ring
$D_2$	154,9 mm	Caliber diameter outer ring
$d_1$	114 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

### Calculation factors

$f_0$	13,3	Calculation factor
-------	------	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides