

**FAG****6322-M**

Deep groove ball bearing

Deep groove ball bearing 63.-M, single row,  
solid brass cage

## Technical information



## Your current product variant

Type of Seal	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	110 mm	Bore diameter
D	240 mm	Outside diameter
B	50 mm	Width
C <sub>r</sub>	201.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	165.000 N	Basic static load rating, radial
C <sub>ur</sub>	8.800 N	Fatigue load limit, radial
n <sub>G</sub>	4.950 1/min	Limiting speed
n <sub>gr</sub>	4.150 1/min	Reference speed
m	11,557 kg	Weight



### Mounting dimensions

$d_{a \min}$	124 mm	Minimum diameter shaft shoulder
$D_{a \max}$	226 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
$D_1$	197,54 mm	Shoulder diameter outer ring
$d_1$	153,26 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Calculation factors

$f_0$	13,8	Calculation factor
-------	------	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed