

**FAG****6316-RSR-C3**

Deep groove ball bearing

Deep groove ball bearing 63...RSR, single row, seal, steel sheet metal cage

Technical information

**Your current product variant**

| | | |
|----------------------------------|--------------|---|
| Type of Sealing | RSR | Contact seal on one side |
| Cage | JN | Steel sheet metal |
| Tolerance class | PN | Normal (PN) |
| Dimensional / heat stabilization | S0 | Rings dimensional stabilized up to 150° |
| Lubricant | Without | Bearing not greased |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Bore type | Z | Cylindrical |

Main Dimensions & Performance Data

| | | |
|-----------------|-------------|-----------------------------------|
| d | 80 mm | Bore diameter |
| D | 170 mm | Outside diameter |
| B | 39 mm | Width |
| C _r | 131.000 N | Basic dynamic load rating, radial |
| C _{0r} | 87.000 N | Basic static load rating, radial |
| C _{ur} | 5.400 N | Fatigue load limit, radial |
| n _G | 2.470 1/min | Limiting speed |
| m | 3,77 kg | Weight |

Mounting dimensions

| | | |
|--------------------|--------|--------------------------------------|
| d _{a min} | 92 mm | Minimum diameter shaft shoulder |
| D _{a max} | 158 mm | Maximum diameter of housing shoulder |
| r _{a max} | 2,1 mm | Maximum fillet radius |



Dimensions

| | | |
|------------|-----------|------------------------------|
| r_{\min} | 2,1 mm | Minimum chamfer dimension |
| D_1 | 141,92 mm | Shoulder diameter outer ring |
| D_2 | 145,48 mm | Caliber diameter outer ring |
| d_1 | 108,2 mm | Shoulder diameter inner ring |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 100 °C | Operating temperature max. |

Calculation factors

| | | |
|-------|------|--------------------|
| f_0 | 13,3 | Calculation factor |
|-------|------|--------------------|

Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Sealed on one side