

**FAG****6322-Z**

Deep groove ball bearing

Deep groove ball bearing 63...-Z, single row, shield, steel sheet metal cage

Technical information



Your current product variant

Sealing	Z	Non-contact shield on one Side
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	110 mm	Bore diameter
D	240 mm	Outside diameter
B	50 mm	Width
C _r	201.000 N	Basic dynamic load rating, radial
C _{0r}	165.000 N	Basic static load rating, radial
C _{ur}	8.800 N	Fatigue load limit, radial
n _G	3.800 1/min	Limiting speed
n _{gr}	4.150 1/min	Reference speed
≈m	10,4 kg	Weight



Mounting dimensions

$d_{a \min}$	124 mm	Minimum diameter shaft shoulder
$D_{a \max}$	226 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum fillet radius

Dimensions

r_{\min}	3 mm	Minimum chamfer dimension
D_1	197,54 mm	Shoulder diameter outer ring
D_2	203,14 mm	Caliber diameter outer ring
d_1	152,85 mm	Shoulder diameter inner ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Calculation factors

f_0	13,8	Calculation factor
-------	------	--------------------

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Sealed on one side