

**FAG****6418-M-C3**

Deep groove ball bearing

Deep groove ball bearing 64...-M, single row, solid brass cage

Technical information



Your current product variant

Sealing	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	90 mm	Bore diameter
D	225 mm	Outside diameter
B	54 mm	Width
C _r	209.000 N	Basic dynamic load rating, radial
C _{0r}	162.000 N	Basic static load rating, radial
C _{ur}	9.100 N	Fatigue load limit, radial
n _G	5.200 1/min	Limiting speed
n _{gr}	4.950 1/min	Reference speed
m	11,7 kg	Weight



Mounting dimensions

$d_{a \min}$	110 mm	Minimum diameter shaft shoulder
$D_{a \max}$	205 mm	Maximum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum fillet radius

Dimensions

r_{\min}	4 mm	Minimum chamfer dimension
D_1	184,14 mm	Shoulder diameter outer ring
d_1	132,1 mm	Shoulder diameter inner ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Calculation factors

f_0	12,1	Calculation factor
-------	------	--------------------

Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed