

**FAG****6020-2RSR-L408-C3**

Deep groove ball bearing

Deep groove ball bearing 60...2RSR, single row, seals, steel sheet metal cage

## Technical information

**Your current product variant**

|                                  |              |   |
|----------------------------------|--------------|---|
| Sealing                          | 2RSR         | Contact seal on both sides              |
| Cage                             | JN           | Steel sheet metal                       |
| Tolerance class                  | PN           | Normal (ISO 492:2023)                   |
| Dimensional / heat stabilization | S0           | Rings dimensional stabilized up to 150° |
| Lubricant                        | L408         | Grease (L408/customer specific)         |
| Radial internal clearance        | C3 (Group 3) | Internal clearance larger than CN       |
| Bore type                        | Z            | Cylindrical                             |

**Main Dimensions & Performance Data**

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 100 mm      | Bore diameter                     |
| D               | 150 mm      | Outside diameter                  |
| B               | 24 mm       | Width                             |
| C <sub>r</sub>  | 64.000 N    | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 54.000 N    | Basic static load rating, radial  |
| C <sub>ur</sub> | 3.050 N     | Fatigue load limit, radial        |
| n <sub>G</sub>  | 2.300 1/min | Limiting speed                    |
| m               | 1,33 kg     | Weight                            |

**Mounting dimensions**

|                    |        |                                      |
|--------------------|--------|--------------------------------------|
| d <sub>a min</sub> | 107 mm | Minimum diameter shaft shoulder      |
| D <sub>a max</sub> | 143 mm | Maximum diameter of housing shoulder |
| r <sub>a max</sub> | 1,5 mm | Maximum fillet radius                |



## Dimensions

|            |           |                              |
|------------|-----------|------------------------------|
| $r_{\min}$ | 1,5 mm    | Minimum chamfer dimension    |
| $D_1$      | 134,12 mm | Shoulder diameter outer ring |
| $D_2$      | 137,3 mm  | Caliber diameter outer ring  |
| $d_1$      | 116,2 mm  | Shoulder diameter inner ring |

## Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 100 °C | Operating temperature max. |

## Calculation factors

|       |      |                    |
|-------|------|--------------------|
| $f_0$ | 15,8 | Calculation factor |
|-------|------|--------------------|

## Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides