

**FAG****6212-2Z-L207-C3**

Deep groove ball bearing

Deep groove ball bearing 62...-2Z, single row, shields, steel sheet metal cage

## Technical information



## Your current product variant

|                                  |              |   |
|----------------------------------|--------------|---|
| Sealing                          | 2Z           | Non-contact shield on both sides                                    |
| Cage                             | JN           | Steel sheet metal   |
| Tolerance class                  | PN           | Normal (PN)   |
| Dimensional / heat stabilization | S0           | Rings dimensional stabilized up to 150°                             |
| Lubricant                        | L207         | Low noise high-temperature grease, interchangeable with grease L069 |
| Radial internal clearance        | C3 (Group 3) | Internal clearance larger than CN                                   |
| Bore type                        | Z            | Cylindrical   |

## Main Dimensions &amp; Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 60 mm       | Bore diameter                     |
| D               | 110 mm      | Outside diameter                  |
| B               | 22 mm       | Width                             |
| C <sub>r</sub>  | 57.000 N    | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 36.500 N    | Basic static load rating, radial  |
| C <sub>ur</sub> | 2.550 N     | Fatigue load limit, radial        |
| n <sub>G</sub>  | 7.900 1/min | Limiting speed                    |
| n <sub>gr</sub> | 6.800 1/min | Reference speed                   |
| m               | 0,775 kg    | Weight                            |



### Mounting dimensions

|              |        |                                      |
|--------------|--------|--------------------------------------|
| $d_{a \min}$ | 69 mm  | Minimum diameter shaft shoulder      |
| $D_{a \max}$ | 101 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 1,5 mm | Maximum fillet radius                |

### Dimensions

|            |          |                              |
|------------|----------|------------------------------|
| $r_{\min}$ | 1,5 mm   | Minimum chamfer dimension    |
| $D_1$      | 95,82 mm | Shoulder diameter outer ring |
| $D_2$      | 97,68 mm | Caliber diameter outer ring  |
| $d_1$      | 75,75 mm | Shoulder diameter inner ring |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 150 °C | Operating temperature max. |

### Calculation factors

|       |      |                    |
|-------|------|--------------------|
| $f_0$ | 14,5 | Calculation factor |
|-------|------|--------------------|

### Characteristics

|   |  |
|---|--|
|  | Radial load                                    |
|  | Axial load in one direction                    |
|  | Axial load in two directions                   |
|  | Lifetime lubrication, freedom from maintenance |
|  | Grease Lubrication                             |
|  | Sealed on both sides                           |