

**FAG****6213-2RSR-L138-C3**

Deep groove ball bearing

Deep groove ball bearing 62...-2RSR, single row, seals, steel sheet metal cage

## Technical information



## Your current product variant

Sealing	2RSR	Contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	L138	Grease (L138/customer specific)
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	65 mm	Bore diameter
D	120 mm	Outside diameter
B	23 mm	Width
C <sub>r</sub>	63.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	41.500 N	Basic static load rating, radial
C <sub>ur</sub>	2.850 N	Fatigue load limit, radial
n <sub>G</sub>	3.250 1/min	Limiting speed
m	0,98 kg	Weight

## Mounting dimensions

d <sub>a min</sub>	74 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	111 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	1,5 mm	Maximum fillet radius



### Dimensions

$r_{min}$	1,5 mm	Minimum chamfer dimension
$D_1$	103,16 mm	Shoulder diameter outer ring
$D_2$	106,34 mm	Caliber diameter outer ring
$d_1$	82 mm	Shoulder diameter inner ring







### Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	100 °C	Operating temperature max.

### Calculation factors

$f_0$	14,4	Calculation factor
-------	------	--------------------

### Characteristics

-   $F_r$  Radial load
-   $F_a$  Axial load in one direction
-   $F_a$  Axial load in two directions
-   $L_h$  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides