

**FAG****6217-N**

Deep groove ball bearing

Deep groove ball bearing 62...-N, single row, ring groove, steel sheet metal cage



## Technical information



## Your current product variant

Sealing	Without	Not sealed
Design, bearing outer ring	N	Ring groove for snap ring
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	85 mm	Bore diameter
D	150 mm	Outside diameter
B	28 mm	Width
C <sub>r</sub>	89.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	64.000 N	Basic static load rating, radial
C <sub>ur</sub>	4.050 N	Fatigue load limit, radial
n <sub>G</sub>	6.700 1/min	Limiting speed
n <sub>gr</sub>	5.300 1/min	Reference speed
≈m	1,838 kg	Weight



### Mounting dimensions

$d_{a \min}$	96 mm	Minimum diameter shaft shoulder
$D_{a \max}$	139 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	2 mm	Minimum chamfer dimension
$D_1$	129,79 mm	Shoulder diameter outer ring
$d_1$	106,58 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Calculation factors

$f_0$	14,8	Calculation factor
-------	------	--------------------

### Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed