

**FAG****62203-A-2RSR-C3**

Deep groove ball bearing

Deep groove ball bearing 622...-A-2RSR,  
single row, steel sheet metal cage

## Technical information

**Your current product variant**

|                                  |                    |   |
|----------------------------------|--------------------|---|
| Changed internal design          | A                  | Design variant A                        |
| Sealing                          | 2RSR               | Contact seal on both sides              |
| Cage                             | JN                 | Steel sheet metal                       |
| Tolerance class                  | PN                 | Normal (PN)                             |
| Dimensional / heat stabilization | SN                 | Rings dimensional stabilized up to 120° |
| Lubricant                        | Lubricating grease |   |
| Radial internal clearance        | C3 (Group 3)       | Internal clearance larger than CN       |
| Bore type                        | Z                  | Cylindrical                             |

**Main Dimensions & Performance Data**

|                 |              |                                   |
|-----------------|--------------|-----------------------------------|
| d               | 17 mm        | Bore diameter                     |
| D               | 40 mm        | Outside diameter                  |
| B               | 16 mm        | Width                             |
| C <sub>r</sub>  | 10.000 N     | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 4.750 N      | Basic static load rating, radial  |
| C <sub>ur</sub> | 355 N        | Fatigue load limit, radial        |
| n <sub>G</sub>  | 11.100 1/min | Limiting speed                    |
| ≈m              | 0,085 kg     | Weight                            |



### Mounting dimensions

|              |         |                                      |
|--------------|---------|--------------------------------------|
| $d_{a \min}$ | 21,2 mm | Minimum diameter shaft shoulder      |
| $D_{a \max}$ | 35,8 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 0,6 mm  | Maximum fillet radius                |

### Dimensions

|            |          |                              |
|------------|----------|------------------------------|
| $r_{\min}$ | 0,6 mm   | Minimum chamfer dimension    |
| $D_1$      | 32,95 mm | Shoulder diameter outer ring |
| $D_2$      | 35,45 mm | Caliber diameter outer ring  |
| $d_1$      | 24,1 mm  | Shoulder diameter inner ring |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -20 °C | Operating temperature min. |
| $T_{\max}$ | 100 °C | Operating temperature max. |

### Calculation factors

|       |    |                    |
|-------|----|--------------------|
| $f_0$ | 13 | Calculation factor |
|-------|----|--------------------|

### Characteristics

|   |  |
|---|--|
|  | Radial load                                    |
|  | Axial load in one direction                    |
|  | Axial load in two directions                   |
|  | Lifetime lubrication, freedom from maintenance |
|  | Grease Lubrication                             |
|  | Sealed on both sides                           |