

**FAG****625-2RSR-HLN**

Deep groove ball bearing

Deep groove ball bearing 62...-2RSR, single row, seals, steel sheet metal cage

Technical information

**Your current product variant**

Logistical code	HLN	-
Sealing	2RSR	Contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Lubricating grease	
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	5 mm	Bore diameter
D	16 mm	Outside diameter
B	5 mm	Width
C _r	1.840 N	Basic dynamic load rating, radial
C _{0r}	670 N	Basic static load rating, radial
C _{ur}	41,5 N	Fatigue load limit, radial
n _G	31.500 1/min	Limiting speed
≈m	4,55 g	Weight



Mounting dimensions

$d_{a \min}$	7,4 mm	Minimum diameter shaft shoulder
$D_{a \max}$	13,6 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,3 mm	Maximum fillet radius

Dimensions

r_{\min}	0,3 mm	Minimum chamfer dimension
D_1	12,5 mm	Shoulder diameter outer ring
D_2	13,5 mm	Caliber diameter outer ring
d_1	8,5 mm	Shoulder diameter inner ring
d_2	7,5 mm	Caliber diameter inner ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.

Calculation factors

f_0	12,4	Calculation factor
-------	------	--------------------

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides