

**FAG****6306-RSR**

Deep groove ball bearing

Deep groove ball bearing 63...RSR, single row, seal, steel sheet metal cage

## Technical information

**Your current product variant**

Type of Seal	RSR	Contact seal on one side
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (PN)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

**Main Dimensions & Performance Data**

d	30 mm	Bore diameter
D	72 mm	Outside diameter
B	19 mm	Width
C <sub>r</sub>	30.500 N	Basic dynamic load rating, radial
C <sub>0r</sub>	16.200 N	Basic static load rating, radial
C <sub>ur</sub>	1.050 N	Fatigue load limit, radial
n <sub>G</sub>	6.000 1/min	Limiting speed
m	0,346 kg	Weight

**Mounting dimensions**

d <sub>a min</sub>	37 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	65 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	1 mm	Maximum fillet radius



### Dimensions

$r_{\min}$	1,1 mm	Minimum chamfer dimension
$D_1$	59,62 mm	Shoulder diameter outer ring
$D_2$	61,58 mm	Caliber diameter outer ring
$d_1$	44,6 mm	Shoulder diameter inner ring







### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

### Calculation factors

$f_0$	13	Calculation factor
-------	----	--------------------

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Sealed on one side