

**FAG****6405-2Z**

Deep groove ball bearing

Deep groove ball bearing 64...-2Z, single row, shields, steel sheet metal cage

## Technical information



## Your current product variant

Sealing	2Z	Non-contact shield on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA13	Ball bearing and insert bearing grease
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	25 mm	Bore diameter
D	80 mm	Outside diameter
B	21 mm	Width
$C_r$	35.500 N	Basic dynamic load rating, radial
$C_{0r}$	19.100 N	Basic static load rating, radial
$C_{ur}$	1.290 N	Fatigue load limit, radial
$n_G$	10.500 1/min	Limiting speed
$n_{gr}$	9.400 1/min	Reference speed
$\approx m$	0,541 kg	Weight



### Mounting dimensions

$d_{a \min}$	36 mm	Minimum diameter shaft shoulder
$D_{a \max}$	69 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1,5 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	1,5 mm	Minimum chamfer dimension
$D_1$	65,6 mm	Shoulder diameter outer ring
$D_2$	67,6 mm	Caliber diameter outer ring
$d_1$	49,3 mm	Shoulder diameter inner ring







### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Calculation factors

$f_0$	13,1	Calculation factor
-------	------	--------------------

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides