





FAG

6224-J20AB-C4

Deep groove ball bearing

Deep groove ball bearing 62...J20AB, single row, steel sheet metal cage, ceramic coated

Technical information



Your current product variant

|                                  |              |                                               |
|----------------------------------|--------------|-----------------------------------------------|
| Type of Seal                     | Without      | Not sealed                                    |
| Cage                             | JN           | Steel sheet metal                             |
| Tolerance class                  | PN           | Normal (ISO 492:2023)                         |
| Dimensional / heat stabilization | S0           | Rings dimensional stabilized up to 150°       |
| Lubricant                        | Without      | Bearing not greased                           |
| Radial internal clearance        | C4 (Group 4) | Internal clearance larger than C3             |
| Bore type                        | Z            | Cylindrical                                   |
| Coating                          | J20AB        | Current insulation, outer ring ceramic coated |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 120 mm      | Bore diameter                     |
| D               | 215 mm      | Outside diameter                  |
| B               | 40 mm       | Width                             |
| C <sub>r</sub>  | 154.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 123.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 6.400 N     | Fatigue load limit, radial        |
| n <sub>G</sub>  | 4.200 1/min | Limiting speed                    |
| n <sub>gr</sub> | 4.250 1/min | Reference speed                   |
| ≈m              | 5,62 kg     | Weight                            |



Mounting dimensions

|             |        |                                      |
|-------------|--------|--------------------------------------|
| $d_{a\min}$ | 132 mm | Minimum diameter shaft shoulder      |
| $D_{a\max}$ | 203 mm | Maximum diameter of housing shoulder |
| $r_{a\max}$ | 2,1 mm | Maximum fillet radius                |

Dimensions

|            |           |                              |
|------------|-----------|------------------------------|
| $r_{\min}$ | 2,1 mm    | Minimum chamfer dimension    |
| $D_1$      | 185,6 mm  | Shoulder diameter outer ring |
| $d_1$      | 151,46 mm | Shoulder diameter inner ring |

Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 150 °C | Operating temperature max. |

Calculation factors

|       |      |                    |
|-------|------|--------------------|
| $f_0$ | 14,8 | Calculation factor |
|-------|------|--------------------|

Characteristics

|                                                                                     |                              |
|-------------------------------------------------------------------------------------|------------------------------|
|  | Radial load                  |
|  | Axial load in one direction  |
|  | Axial load in two directions |
|  | Grease Lubrication           |
|  | Oil Lubrication              |
|  | Not sealed                   |
|  | Current insulated            |