

**FAG****6215-M-J20AA-C4**

Deep groove ball bearing

Deep groove ball bearing 62...-M-J20AA,
single row, solid brass cage, ceramic coated

Technical information



Your current product variant

| | | |
|----------------------------------|--------------|---|
| Sealing | Without | Not sealed |
| Cage | M | Solid brass cage, rolling element guided |
| Tolerance class | PN | Normal (ISO 492:2023) |
| Dimensional / heat stabilization | S0 | Rings dimensional stabilized up to 150° |
| Lubricant | Without | Bearing not greased |
| Radial internal clearance | C4 (Group 4) | Internal clearance larger than C3 |
| Bore type | Z | Cylindrical |
| Coating | J20AA | Current insulation, outer ring ceramic coated |

Main Dimensions & Performance Data

| | | |
|-----------------|--------------|-----------------------------------|
| d | 75 mm | Bore diameter |
| D | 130 mm | Outside diameter |
| B | 25 mm | Width |
| C _r | 70.000 N | Basic dynamic load rating, radial |
| C _{0r} | 49.000 N | Basic static load rating, radial |
| C _{ur} | 3.300 N | Fatigue load limit, radial |
| n _G | 10.200 1/min | Limiting speed |
| n _{gr} | 5.900 1/min | Reference speed |
| ≈m | 1,34 kg | Weight |



Mounting dimensions

| | | |
|--------------|--------|--------------------------------------|
| $d_{a \min}$ | 84 mm | Minimum diameter shaft shoulder |
| $D_{a \max}$ | 121 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 1,5 mm | Maximum fillet radius |

Dimensions

| | | |
|------------|----------|------------------------------|
| r_{\min} | 1,5 mm | Minimum chamfer dimension |
| D_1 | 113,3 mm | Shoulder diameter outer ring |
| d_1 | 92,1 mm | Shoulder diameter inner ring |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 150 °C | Operating temperature max. |

Calculation factors

| | | |
|-------|------|--------------------|
| f_0 | 14,6 | Calculation factor |
|-------|------|--------------------|

Characteristics

| | |
|---|------------------------------|
|  | Radial load |
|  | Axial load in one direction |
|  | Axial load in two directions |
|  | Grease Lubrication |
|  | Oil Lubrication |
|  | Not sealed |
|  | Current insulated |