

**FAG****6315-J20AB-C3**

Deep groove ball bearing

Deep groove ball bearing 63..-J20AB, single row, steel sheet metal cage, ceramic coated

## Technical information



## Your current product variant

Type of Seal	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical
Coating	J20AB	Current insulation, outer ring ceramic coated

## Main Dimensions &amp; Performance Data

d	75 mm	Bore diameter
D	160 mm	Outside diameter
B	37 mm	Width
C <sub>r</sub>	123.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	77.000 N	Basic static load rating, radial
C <sub>ur</sub>	4.850 N	Fatigue load limit, radial
n <sub>G</sub>	6.300 1/min	Limiting speed
n <sub>gr</sub>	5.800 1/min	Reference speed
≈m	3,06 kg	Weight



### Mounting dimensions

$d_{a \min}$	87 mm	Minimum diameter shaft shoulder
$D_{a \max}$	148 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	2,1 mm	Minimum chamfer dimension
$D_1$	133,8 mm	Shoulder diameter outer ring
$d_1$	101,77 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Calculation factors

$f_0$	13,2	Calculation factor
-------	------	--------------------

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Current insulated