

**FAG****4201-BB-TVH**

## Deep groove ball bearing

Deep groove ball bearing 42...-BB-TVH,  
double row, plastic cage



## Technical information

## Your current product variant

Design variant	B	Bearing without filling slot
Tolerance class	PN	Normal (ISO 492:2023)
Changed internal design	B	B
Cage	TVH	Solid cage made of glass-fiber reinforced polyamid PA66
Lubricant	GA14	Ball bearing grease, low noise
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Radial internal clearance	CN (Group N)	Normal internal clearance

## Main Dimensions &amp; Performance Data

d	12 mm	Bore diameter
D	32 mm	Outside diameter
B	14 mm	Width
$C_r$	11.100 N	Basic dynamic load rating, radial
$C_{0r}$	6.100 N	Basic static load rating, radial
$C_{ur}$	320 N	Fatigue load limit, radial
$n_G$	22.300 1/min	Limiting speed
$n_{gr}$	19.100 1/min	Reference speed
$\approx m$	0,051 kg	Weight





### Mounting dimensions

$d_{a \min}$	16,2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	27,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,6 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	0,6 mm	Minimum chamfer dimension
$D_1$	25,94 mm	Shoulder diameter outer ring
$d_1$	17,8 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Calculation factors

$f_0$	12,3	Calculation factor
-------	------	--------------------

### Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Not sealed