

**FAG****4311-B-TVH**

Deep groove ball bearing

Deep groove ball bearing 43..-B-TVH, double row, plastic cage

Technical information



Your current product variant

Design variant	B	Bearing without filling slot
Tolerance class	PN	Normal (PN)
Cage	TVH	Solid cage made of glass-fiber reinforced polyamid PA66
Lubricant	Lubricating grease	
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Radial internal clearance	CN (Group N)	Normal internal clearance

Main Dimensions & Performance Data

d	55 mm	Bore diameter
D	120 mm	Outside diameter
B	43 mm	Width
C_r	111.000 N	Basic dynamic load rating, radial
C_{0r}	90.000 N	Basic static load rating, radial
C_{ur}	5.600 N	Fatigue load limit, radial
n_G	5.100 1/min	Limiting speed
n_{gr}	4.650 1/min	Reference speed
$\approx m$	2,06 kg	Weight

Mounting dimensions

$d_{a \min}$	66 mm	Minimum diameter shaft shoulder
$D_{a \max}$	109 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2 mm	Maximum fillet radius



Dimensions

r_{\min}	2 mm	Minimum chamfer dimension
D_1	105,3 mm	Shoulder diameter outer ring
d_1	80,35 mm	Shoulder diameter inner ring






Temperature range

T_{\min}	-20 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Calculation factors

f_0	13,8	Calculation factor
-------	------	--------------------

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Not sealed