

**E20-XL-KRR**

## Radial insert ball bearing

Radial insert ball bearings E...KRR,  
cylindrical outer ring, location by eccentric  
locking collar, R seals on both sides

X-life

## Technical information

**Main Dimensions & Performance Data**

d	20 mm	Bore diameter
D	47 mm	Outside diameter
B	34,1 mm	Width
B <sub>1</sub>	43,7 mm	Locking collar total width
C <sub>r</sub>	12.800 N	Basic dynamic load rating, radial
C <sub>0r</sub>	6.600 N	Basic static load rating, radial
C <sub>ur</sub>	345 N	Fatigue load limit, radial
≈m	0,2 kg	Weight

**Dimensions**

C	14 mm	Width, outer ring
C <sub>2</sub>	16,6 mm	Sealing total width
S	17,1 mm	Distance raceway
d <sub>1</sub>	27,6 mm	Rib diameter inner ring
D <sub>1</sub>	37,4 mm	Outside diameter seal
d <sub>3</sub>	33 mm	Outside diameter locking collar/locknut
W	3 mm	Width of flats







**Calculation factors**

f <sub>0</sub>	13,1	Calculation factor
----------------	------	--------------------



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides