


**GE40-KRR-B-L285/50-OSE** [↗](#)

Radial insert ball bearing

Radial insert ball bearing GE...KRR-B-L285/70-OSE

## Technical information

**Your current product variant**

Lubricant	L285/50	Grease (L285/50)
-----------	---------	------------------

**Main Dimensions & Performance Data**

d	40 mm	Bore diameter
D <sub>SP</sub>	80 mm	Outside diameter
B	42,9 mm	Width
C <sub>0r</sub>	19.800 N	Basic static load rating, radial
C <sub>ur</sub>	840 N	Fatigue load limit, radial
C <sub>r</sub>	32.500 N	Basic dynamic load rating, radial
≈m	0,57 kg	Weight

**Dimensions**

C	21 mm	Width, outer ring
C <sub>2</sub>	23,5 mm	Sealing total width
S	21,4 mm	Distance raceway
d <sub>1</sub>	52,3 mm	Rib diameter inner ring
D <sub>1</sub>	68,3 mm	Outside diameter seal
C <sub>a</sub>	6,4 mm	Distance to lubrication hole

**Temperature range**

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.



### Calculation factors

---

$f_0$	13,6	Calculation factor
-------	------	--------------------

### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment