
**PE35-XL**

## Radial insert ball bearing

Radial insert ball bearings PE, cylindrical outer ring, with steel aligning ring, location by eccentric locking collar, P seals on both sides

X-life

## Technical information

**Main Dimensions & Performance Data**

d	35 mm	Bore diameter
D	80 mm	Outside diameter
U	40 mm	Width
$C_r$	25.500 N	Basic dynamic load rating, radial
$C_{0r}$	15.300 N	Basic static load rating, radial
$C_{ur}$	650 N	Fatigue load limit, radial
$\approx m$	0,63 kg	Weight

**Dimensions**

A	21 mm	Width, outer ring
$C_1$	14,4 mm	Distance ring grooves
	0,2 mm	Upper distance ring groove tolerance
b	1,9 mm	Width retaining slot
	0,3 mm	Nut width upper tolerance
$D_1$	76,8 mm	Diameter of groove
	-0,5 mm	Nut diameter lower tolerance

**Calculation factors**

$f_0$	13,8	Calculation factor
-------	------	--------------------



### Additional information

---

RAE35-XL-NPP-B

Bearing designation

### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides



Static angular error and misalignment