
**CRB25/72-XL**

## Radial insert ball bearing

Radial insert ball bearings CRB, with rubber interliner, location by eccentric locking collar, P seals on both sides

X-life

## Technical information

**Main Dimensions & Performance Data**

d	25 mm	Bore diameter
D	73 mm	Outside diameter
C	25 mm	Width, outer ring
B <sub>2</sub>	36 mm	Width total
B <sub>1</sub>	31 mm	Locking collar total width
C <sub>r</sub>	14.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	7.800 N	Basic static load rating, radial
C <sub>ur</sub>	370 N	Fatigue load limit, radial
	1.000 N	Load carrying capacity (rubber interliner)
≈m	0,27 kg	Weight

**Dimensions**

D <sub>1</sub>	80 mm	Flange diameter
C <sub>1</sub>	5 mm	Thickness of flange
D <sub>2</sub>	46 mm	Flange diameter rubber interliner
d <sub>3</sub>	37,5 mm	Outside diameter locking collar/locknut
S <sub>2</sub>	12,5 mm	Distance raceway to rubber interliner flange side

**Calculation factors**







f <sub>0</sub>	13,8	Calculation factor
----------------	------	--------------------



### Additional information

	RAE25-XL-NPP	Bearing designation
Shore A	80 °	Hardness rubber interliner

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides