


**RABRB15/47-XL-FA106**

Radial insert ball bearing

Radial insert ball bearings RABR, with rubber interliner, location by eccentric locking collar, P seals on both sides

X-life

## Technical information



## Your current product variant

Manufacturing instruction	FA106	Bearing subjected to special noise testing
---------------------------	-------	--

## Main Dimensions &amp; Performance Data

d	15 mm	Bore diameter
D	47,3 mm	Outside diameter
C	18 mm	Width, outer ring
B <sub>2</sub>	31,1 mm	Width total
B <sub>1</sub>	28,6 mm	Locking collar total width
C <sub>r</sub>	9.800 N	Basic dynamic load rating, radial
C <sub>0r</sub>	4.750 N	Basic static load rating, radial
C <sub>ur</sub>	248 N	Fatigue load limit, radial
	840 N	Load carrying capacity (rubber interliner)
≈m	0,2 kg	Weight

## Dimensions

S <sub>1</sub>	22,1 mm	Distance raceway to locking collar
D <sub>2</sub>	33,5 mm	Flange diameter rubber interliner
d <sub>3</sub>	28,4 mm	Outside diameter locking collar/locknut










### Calculation factors

$f_0$	13	Calculation factor
-------	----	--------------------

### Additional information

	RAE15-XL-NPP-B-FA106	Bearing designation
Shore A	70 °	Hardness rubber interliner

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment