
**RCRB25/57-XL-FA106** [↗](#)

Radial insert ball bearing

Radial insert ball bearings RCR, with rubber interliner, location by eccentric locking collar, P seals on both sides

X-life

Technical information



Your current product variant

Manufacturing instruction	FA106	Bearing subjected to special noise testing
---------------------------	-------	--

Main Dimensions & Performance Data

d	25 mm	Bore diameter
D	57,3 mm	Outside diameter
C	19,8 mm	Width, outer ring
B ₁	31 mm	Locking collar total width
C _r	14.000 N	Basic dynamic load rating, radial
C _{0r}	7.800 N	Basic static load rating, radial
C _{ur}	370 N	Fatigue load limit, radial
	1.400 N	Load carrying capacity (rubber interliner)
≈m	0,202 kg	Weight

Dimensions

C ₂	17,5 mm	Width outside profile of rubber interliner
S ₁	23,5 mm	Distance raceway to locking collar
D ₂	44,5 mm	Flange diameter rubber interliner
d ₃	37,5 mm	Outside diameter locking collar/locknut
P	9,8 mm	Distance raceway of rubber interliner to face side



Calculation factors

f ₀	13,8	Calculation factor
----------------	------	--------------------

Additional information

RAE25-XL-NPP- FA106	Bearing designation
------------------------	---------------------

Shore A	70 °	Hardness rubber interliner
---------	------	----------------------------