
**RCSMA30/65-XL-FA106**

Radial insert ball bearing

Radial insert ball bearings RCSM, with rubber interliner, location by eccentric locking collar, P seals on both sides

X-life

Technical information



Your current product variant

Manufacturing instruction	FA106	Bearing subjected to special noise testing
---------------------------	-------	--

Main Dimensions & Performance Data

d	30 mm	Bore diameter
D	65,1 mm	Outside diameter
C	25,4 mm	Width, outer ring
B ₁	26,5 mm	Locking collar total width
C _r	13.200 N	Basic dynamic load rating, radial
C _{0r}	8.300 N	Basic static load rating, radial
C _{ur}	430 N	Fatigue load limit, radial
	1.400 N	Load carrying capacity (rubber interliner)
≈m	0,219 kg	Weight

Dimensions

S ₁	20 mm	Distance raceway to locking collar
D ₂	47,6 mm	Flange diameter rubber interliner
d ₃	42,5 mm	Outside diameter locking collar/locknut
P	15 mm	Distance raceway of rubber interliner to face side



Calculation factors

f ₀	14,8	Calculation factor
----------------	------	--------------------

Additional information

	RALE30-XL-NPP- FA106	Bearing designation
--	-------------------------	---------------------

Shore A	70 °	Hardness rubber interliner
---------	------	----------------------------