
**RCSMB15/65-XL-FA106**

## Radial insert ball bearing

Radial insert ball bearings RCSM, with rubber interliner, location by eccentric locking collar, P seals on both sides

X-life

## Technical information



## Your current product variant

Manufacturing instruction	FA106	Bearing subjected to special noise testing
---------------------------	-------	--------------------------------------------

## Main Dimensions &amp; Performance Data

d	15 mm	Bore diameter
D	65,1 mm	Outside diameter
C	25,4 mm	Width, outer ring
B <sub>1</sub>	28,6 mm	Locking collar total width
C <sub>r</sub>	10.100 N	Basic dynamic load rating, radial
C <sub>0r</sub>	4.750 N	Basic static load rating, radial
C <sub>ur</sub>	248 N	Fatigue load limit, radial
	900 N	Load carrying capacity (rubber interliner)
≈m	0,195 kg	Weight

## Dimensions

S <sub>1</sub>	22,1 mm	Distance raceway to locking collar
D <sub>2</sub>	35 mm	Flange diameter rubber interliner
d <sub>3</sub>	28,4 mm	Outside diameter locking collar/locknut
P	12,7 mm	Distance raceway of rubber interliner to face side



### Calculation factors

---

f <sub>0</sub>	13	Calculation factor
----------------	----	--------------------

### Additional information

---

RAE15-XL-NPP-FA106	Bearing designation
--------------------	---------------------

Shore A	70 °	Hardness rubber interliner
---------	------	----------------------------