

**GE65-214-XL-KRR-B-FA164**

Radial insert ball bearing

Radial insert ball bearings GE...KRR-B-FA164, spherical outer ring, location by eccentric locking collar, R seals on both sides, for temperatures up to +250°C

X-life

Technical information



Your current product variant

Manufacturing instruction

FA164

High temperature design up to +250°C

Main Dimensions & Performance Data

d	65 mm	Bore diameter
D _{SP}	125 mm	Outside diameter
B	48,5 mm	Width
C _{0r}	44.000 N	Basic static load rating, radial
C _{ur}	2.090 N	Fatigue load limit, radial
B ₁	66 mm	Locking collar total width
C _r	62.000 N	Basic dynamic load rating, radial
≈m	2,42 kg	Weight










Dimensions

C	28 mm	Width, outer ring
C ₂	32 mm	Sealing total width
S	21,5 mm	Distance raceway
d ₁	85,2 mm	Rib diameter inner ring
D ₁	109 mm	Outside diameter seal
C _a	8,9 mm	Distance to lubrication hole
d ₃	96 mm	Outside diameter locking collar/locknut
W	6 mm	Width of flats

Calculation factors

f ₀	14,4	Calculation factor
----------------	------	--------------------

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment