

**GE20-XL-KRR-B-FA125**

Radial insert ball bearing

Radial insert ball bearing GE...XL-KRR-B

X-life

Technical information

**Main Dimensions & Performance Data**

d	20 mm	Bore diameter
D _{SP}	47 mm	Outside diameter
B	34,1 mm	Width
C _{0r}	6.600 N	Basic static load rating, radial
C _{ur}	315 N	Fatigue load limit, radial
B ₁	43,7 mm	Locking collar total width
C _r	12.800 N	Basic dynamic load rating, radial
≈m	0,19 kg	Weight

Dimensions

C	14 mm	Width, outer ring
C ₂	16,6 mm	Sealing total width
S	17,1 mm	Distance raceway
d ₁	27,6 mm	Rib diameter inner ring
D ₁	37,4 mm	Outside diameter seal
C _a	4 mm	Distance to lubrication hole
d ₃	33 mm	Outside diameter locking collar/locknut
W	3 mm	Width of flats



Calculation factors

f_0	13,1	Calculation factor
-------	------	--------------------

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment