

**GE25-XL-KRR-B-FA125**

Radial insert ball bearing

Radial insert ball bearing GE...XL-KRR-B

X-life

## Technical information

**Main Dimensions & Performance Data**

d	25 mm	Bore diameter
D <sub>SP</sub>	52 mm	Outside diameter
B	34,9 mm	Width
C <sub>0r</sub>	7.800 N	Basic static load rating, radial
C <sub>ur</sub>	370 N	Fatigue load limit, radial
B <sub>1</sub>	44,5 mm	Locking collar total width
C <sub>r</sub>	14.900 N	Basic dynamic load rating, radial
≈m	0,24 kg	Weight

**Dimensions**

C	15 mm	Width, outer ring
C <sub>2</sub>	16,7 mm	Sealing total width
S	17,5 mm	Distance raceway
d <sub>1</sub>	33,8 mm	Rib diameter inner ring
D <sub>1</sub>	42,5 mm	Outside diameter seal
C <sub>a</sub>	4,1 mm	Distance to lubrication hole
d <sub>3</sub>	37,5 mm	Outside diameter locking collar/locknut
W	3 mm	Width of flats



### Calculation factors

---

$f_0$	13,8	Calculation factor
-------	------	--------------------

### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment