

**GE40-XL-KRR-B-FA164**

Radial insert ball bearing

Radial insert ball bearings GE...KRR-B-FA164, spherical outer ring, location by eccentric locking collar, R seals on both sides, for temperatures up to +250°C

X-life

## Technical information



## Your current product variant

Manufacturing instruction

FA164

High temperature design up to +250°C

## Main Dimensions &amp; Performance Data

d	40 mm	Bore diameter
D <sub>SP</sub>	80 mm	Outside diameter
B	42,9 mm	Width
C <sub>0r</sub>	19.800 N	Basic static load rating, radial
C <sub>ur</sub>	940 N	Fatigue load limit, radial
B <sub>1</sub>	56,5 mm	Locking collar total width
C <sub>r</sub>	32.500 N	Basic dynamic load rating, radial
m	0,75 kg	Weight



## Dimensions

C	21 mm	Width, outer ring
C <sub>2</sub>	23,5 mm	Sealing total width
S	21,4 mm	Distance raceway
d <sub>1</sub>	52,3 mm	Rib diameter inner ring
D <sub>1</sub>	68,3 mm	Outside diameter seal
C <sub>a</sub>	6,4 mm	Distance to lubrication hole
d <sub>3</sub>	58 mm	Outside diameter locking collar/locknut
W	5 mm	Width of flats








## Temperature range

T <sub>min</sub>	150 °C	Operating temperature min.
T <sub>max</sub>	250 °C	Operating temperature max.

## Calculation factors

f <sub>0</sub>	13,6	Calculation factor
----------------	------	--------------------

## Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides
	Static angular error and misalignment