


**GLE25-XL-KRR-B**

Radial insert ball bearing

Radial insert ball bearings GLE...KRR-B, spherical outer ring, non-locating bearing, drive slot in inner ring, R seals on both sides

X-life

## Technical information

**Main Dimensions & Performance Data**

d	25 mm	Bore diameter
D <sub>SP</sub>	52 mm	Outside diameter
B	34,9 mm	Width
C <sub>0r</sub>	7.800 N	Basic static load rating, radial
C <sub>ur</sub>	410 N	Fatigue load limit, radial
C <sub>r</sub>	14.000 N	Basic dynamic load rating, radial
≈m	0,19 kg	Weight

**Dimensions**

C	15 mm	Width, outer ring
C <sub>2</sub>	16,7 mm	Sealing total width
S	14,7 mm	Distance raceway
d <sub>1</sub>	33,8 mm	Rib diameter inner ring
D <sub>1</sub>	42,5 mm	Outside diameter seal
C <sub>a</sub>	3,9 mm	Distance to lubrication hole
N	8 mm	Hight retaining slot
b	7 mm	Width retaining slot
	H11	Width retaining slot clearance



### Calculation factors

---

$f_0$	13,8	Calculation factor
-------	------	--------------------

### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment