


**GLE30-XL-KRR-B** [↗](#)

Radial insert ball bearing

Radial insert ball bearings GLE..-KRR-B,
spherical outer ring, non-locating bearing,
drive slot in inner ring, R seals on both sides

X-life

Technical information

**Main Dimensions & Performance Data**

d	30 mm	Bore diameter
D _{SP}	62 mm	Outside diameter
B	36,5 mm	Width
C _{0r}	11.300 N	Basic static load rating, radial
C _{ur}	520 N	Fatigue load limit, radial
C _r	19.500 N	Basic dynamic load rating, radial
≈m	0,3 kg	Weight

Dimensions

C	18 mm	Width, outer ring
C ₂	19,8 mm	Sealing total width
S	14,5 mm	Distance raceway
d ₁	40,2 mm	Rib diameter inner ring
D ₁	52 mm	Outside diameter seal
C _a	4,7 mm	Distance to lubrication hole
N	8 mm	Hight retaining slot
b	7 mm	Width retaining slot
	H11	Width retaining slot clearance



Calculation factors

f_0	13,8	Calculation factor
-------	------	--------------------

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment