

**GNE40-XL-KRR-B**

## Radial insert ball bearing

Radial insert ball bearings GNE...KRR-B, spherical outer ring, location by eccentric locking collar, R seals on both sides

X-life

## Technical information

**Main Dimensions & Performance Data**

d	40 mm	Bore diameter
D <sub>SP</sub>	90 mm	Outside diameter
B	41 mm	Width
C <sub>0r</sub>	26.000 N	Basic static load rating, radial
C <sub>ur</sub>	1.360 N	Fatigue load limit, radial
B <sub>1</sub>	54,6 mm	Locking collar total width
C <sub>r</sub>	47.000 N	Basic dynamic load rating, radial
≈m	1,02 kg	Weight

**Dimensions**

C	23 mm	Width, outer ring
C <sub>2</sub>	26 mm	Sealing total width
S	18 mm	Distance raceway
d <sub>1</sub>	53,8 mm	Rib diameter inner ring
D <sub>1</sub>	74,5 mm	Outside diameter seal
C <sub>a</sub>	7,5 mm	Distance to lubrication hole
d <sub>3</sub>	63 mm	Outside diameter locking collar/locknut
W	5 mm	Width of flats



### Calculation factors

---

$f_0$	12,9	Calculation factor
-------	------	--------------------

### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment