

**GRAE17-XL-NPP-B**

Radial insert ball bearing

Radial insert ball bearing GRAE...XL-NPP-B

X-life

Technical information

**Main Dimensions & Performance Data**

| | | |
|-----------------|---------|-----------------------------------|
| d | 17 mm | Bore diameter |
| D _{SP} | 40 mm | Outside diameter |
| B | 19 mm | Width |
| C _{0r} | 4.750 N | Basic static load rating, radial |
| C _{ur} | 248 N | Fatigue load limit, radial |
| B ₁ | 28,6 mm | Locking collar total width |
| C _r | 9.800 N | Basic dynamic load rating, radial |
| ≈m | 0,1 kg | Weight |

Dimensions

| | | |
|----------------|---------|---|
| C | 12 mm | Width, outer ring |
| S | 6,5 mm | Distance raceway |
| d ₂ | 23 mm | Rib diameter sealing inner ring |
| C _a | 3,4 mm | Distance to lubrication hole |
| d ₃ | 28,4 mm | Outside diameter locking collar/locknut |
| W | 3 mm | Width of flats |

Calculation factors

| | | |
|----------------|----|--------------------|
| f ₀ | 13 | Calculation factor |
|----------------|----|--------------------|



Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment