

**GYE35-XL-KRR-B**

Radial insert ball bearing

Radial insert ball bearings GYE...-KRR-B,  
spherical outer ring, location by grub screws,  
R seals on both sides

X-life

## Technical information

**Main Dimensions & Performance Data**

d	35 mm	Bore diameter
D <sub>SP</sub>	72 mm	Outside diameter
B	42,9 mm	Width
C <sub>0r</sub>	15.300 N	Basic static load rating, radial
C <sub>ur</sub>	650 N	Fatigue load limit, radial
C <sub>r</sub>	25.500 N	Basic dynamic load rating, radial
≈m	0,44 kg	Weight

**Dimensions**

C	19 mm	Width, outer ring
C <sub>2</sub>	22,5 mm	Sealing total width
S	17,5 mm	Distance raceway
d <sub>1</sub>	46,8 mm	Rib diameter inner ring
D <sub>1</sub>	60,3 mm	Outside diameter seal
C <sub>a</sub>	5,6 mm	Distance to lubrication hole
A	6 mm	Distance thread
W	3 mm	Width of flats

**Calculation factors**

f <sub>0</sub>	13,8	Calculation factor
----------------	------	--------------------



## Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides



Static angular error and misalignment