

**RALE30-XL-NPP-B**

## Radial insert ball bearing

Radial insert ball bearings RALE...NPP-B, spherical outer ring, location by eccentric locking collar, P seals on both sides

X-life

## Technical information

**Main Dimensions & Performance Data**

d	30 mm	Bore diameter
D <sub>SP</sub>	55 mm	Outside diameter
B	18,5 mm	Width
C <sub>0r</sub>	8.300 N	Basic static load rating, radial
C <sub>ur</sub>	430 N	Fatigue load limit, radial
B <sub>1</sub>	26,5 mm	Locking collar total width
C <sub>r</sub>	13.200 N	Basic dynamic load rating, radial
≈m	0,18 kg	Weight

**Dimensions**

C	13 mm	Width, outer ring
S	6,5 mm	Distance raceway
d <sub>2</sub>	35,7 mm	Rib diameter sealing inner ring
d <sub>3</sub>	42,5 mm	Outside diameter locking collar/locknut
W	2,5 mm	Width of flats

**Calculation factors**

f <sub>0</sub>	14,8	Calculation factor
----------------	------	--------------------



## Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment