



**FAG****UK207**

Radial insert ball bearing

Radial insert ball bearings UK, spherical outer ring, location by adapter sleeve, RSR seals on both sides

Technical information

**Main Dimensions & Performance Data**

D _{SP}	72 mm	Outside diameter
B	29 mm	Width
C _{0r}	15.300 N	Basic static load rating, radial
C _{ur}	800 N	Fatigue load limit, radial
C _r	27.500 N	Basic dynamic load rating, radial
≈m	0,54 kg	Weight

Dimensions

C	20 mm	Width, outer ring
C ₂	20,6 mm	Sealing total width
C _a	5,7 mm	Distance to lubrication hole
d ₃	52 mm	Outside diameter locking collar/locknut
B ₂	9 mm	Width nut and lock

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Calculation factors




f ₀	13,8	Calculation factor
----------------	------	--------------------



Additional information

H2307-J30QH	Adapter sleeve
KM7	Locknut
MB7	Fuse
H.H2307	Sleeve

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment