


**FAG****UK218**

## Radial insert ball bearing

Radial insert ball bearings UK, spherical outer ring, location by adapter sleeve, RSR seals on both sides

## Technical information

**Main Dimensions & Performance Data**

$D_{SP}$	160 mm	Outside diameter
B	51 mm	Width
$C_{0r}$	72.000 N	Basic static load rating, radial
$C_{ur}$	3.350 N	Fatigue load limit, radial
$C_r$	102.000 N	Basic dynamic load rating, radial
$\approx m$	4,62 kg	Weight

**Dimensions**

C	38 mm	Width, outer ring
$C_2$	39,4 mm	Sealing total width
$C_a$	11 mm	Distance to lubrication hole
$d_3$	120 mm	Outside diameter locking collar/locknut
$B_2$	18 mm	Width nut and lock

**Temperature range**

$T_{min}$	-20 °C	Operating temperature min.
$T_{max}$	120 °C	Operating temperature max.

**Calculation factors**




$f_0$	14,6	Calculation factor
-------	------	--------------------



### Additional information

H2318-J30QH	Adapter sleeve
KM18	Locknut
MB18	Fuse
H.H2318	Sleeve

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment