


**GRAE55-NPP-B-FA107** [↗](#)

Radial insert ball bearing

Radial insert ball bearing GRAE...NPP-B

## Technical information

**Main Dimensions & Performance Data**

d	55 mm	Bore diameter
D <sub>SP</sub>	100 mm	Outside diameter
B	32,5 mm	Width
C <sub>0r</sub>	29.000 N	Basic static load rating, radial
C <sub>ur</sub>	1.340 N	Fatigue load limit, radial
B <sub>1</sub>	48,4 mm	Locking collar total width
C <sub>r</sub>	43.500 N	Basic dynamic load rating, radial
≈m	1,06 kg	Weight

**Dimensions**

C	25 mm	Width, outer ring
S	12,5 mm	Distance raceway
d <sub>2</sub>	66 mm	Rib diameter sealing inner ring
d <sub>3</sub>	76 mm	Outside diameter locking collar/locknut
W	5 mm	Width of flats

**Temperature range**

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.



### Calculation factors

---

$f_0$	14,2	Calculation factor
-------	------	--------------------

### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment