


**GYE30-KRR-B-FA107**

Radial insert ball bearing

Radial insert ball bearing GYE...KRR-B

## Technical information

**Main Dimensions & Performance Data**

d	30 mm	Bore diameter
D <sub>SP</sub>	62 mm	Outside diameter
B	38,1 mm	Width
C <sub>0r</sub>	11.300 N	Basic static load rating, radial
C <sub>ur</sub>	480 N	Fatigue load limit, radial
C <sub>r</sub>	19.500 N	Basic dynamic load rating, radial
≈m	0,3 kg	Weight

**Dimensions**

C	18 mm	Width, outer ring
C <sub>2</sub>	20,7 mm	Sealing total width
S	15,9 mm	Distance raceway
d <sub>1</sub>	40,2 mm	Rib diameter inner ring
D <sub>1</sub>	52 mm	Outside diameter seal
C <sub>a</sub>	4,7 mm	Distance to lubrication hole
A	5,8 mm	Distance thread
W	3 mm	Width of flats

**Temperature range**

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.



### Calculation factors

---

$f_0$	13,8	Calculation factor
-------	------	--------------------

### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment