


IMAGE
COMING SOON**GRA104-NPP-B-AS2/V**

Radial insert ball bearing

Radial insert ball bearing GRA..-NPP-B-AS2/
V

Technical information



Your current product variant

Sealing	NPP	Lip seal on both sides
Shape of outer surface	B	
Lubrication hole transposed	AS2/V	AS2/V

Main Dimensions & Performance Data

d	31,75 mm	Bore diameter
d	31,75 mm	Bore diameter, inch
D _{SP}	72 mm	Outside diameter
B ₁	39 mm	Locking collar total width
B	25,4 mm	Width
C _{ur}	800 N	Fatigue load limit, radial
C _r	25.500 N	Basic dynamic load rating, radial
C _{0r}	15.300 N	Basic static load rating, radial
≈m	0,494 kg	Weight










Dimensions

C	19 mm	Width, outer ring
S	9,5 mm	Distance raceway
d ₂	44,5 mm	Rib diameter sealing inner ring
C _a	5,7 mm	Distance to lubrication hole
d ₃	51 mm	Outside diameter locking collar/locknut
W	4,762 mm	Width across flats (Inch)

Calculation factors

f ₀	13,8	Calculation factor
----------------	------	--------------------

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment